



We are committed to  
Reducing your maintenance cost!™



## **PENETRATING LUBRICANT EXTREME PRESSURE**

### **ADVANTAGES**

**EXTREME PRESSURE  
DEHUMIDIFIES  
PREVENTS RUST  
LUBRICATES  
CLEANSES IN DEPTH  
DIELECTRIC STRENGTH 38 kV  
WORKS UP TO - 45°C (- 49°F)**

### **REACTION**

The unique formula of Lubri-Lab's **PenLub Original** is a combination of essential ingredients necessary in order to cleanse, lubricate and protect metal. **PenLub Original** lubricates sensitive mechanical, electrical and electronic devices. **PenLub Original** does not attract dust or dirt and does not become oxidized under high temperatures. Its superior anti-corrosive properties permit storage up to one year of large reservoirs, tools, accessories and electrical equipment. Excellent for every general and specialized needs. **PenLub Original** is a Silicone free product that is harmless to plastics, metals and isolated parts. Treated parts may be painted, plated or welded.

With only one application **PenLub Original** penetrates the metal pores, disperses humidity, eliminates rust and metal flakes cleans away grease and dirt while leaving behind a fine lubricating protective film.

**PenLub Original** may be sprayed on damp electric and electronic systems to rapidly get them back in good working order, while leaving a thin film which inhibits rust, for prolonged protection.



We are committed to  
Reducing your maintenance cost!™



## PENETRATING LUBRICANT EXTREME PRESSURE

### APPLICATIONS

- Motors and generators
- Locks
- Fans
- Circuit breakers, integrated and switches
- Mine and Marine equipment
- Elevators
- Assembly line
- Penetrating fluid
- Antifriction applications
- Pneumatic tools & systems
- Sprinklers
- Many, many more

### ADVANTAGES

- Dielectric:
  - Aerosol.....14.7 kV
  - Bulk liquid..... 29.8 kV
- Antifriction
- Dissipates moisture
- Prevents rust
- Lubricates
- Cleanses in depth
- Does not harm plastic
- Does not attract dust, dirt, or airborne pollutants
- Safe for integrated circuitry
- Silicone free
- Food approved standard H-2, CFIA No. :/L125

Our solenoids and valves were constantly jamming because of water contamination from the humidity and air compressor. Some months we had to replace as much as 15 solenoids, at roughly 500\$ each. Now, since we are using PENLUB as our pneumatic oil. We rarely have to change any solenoid. Saving us as much as 45,000\$ USD. We are astonished by the results of this product.

P.T.TIRTA LYONNAISE MEDAN  
Sugiono Andiato  
Maintenance Manager.

Test Dielectric Rigidity : - **PenLub Original aerosol** (kV) D877 : 14.7 kV (14 700 volts)  
- **PenLub Original bulk** (kV) D877 : 29.8 kV (29 800 volts)

**Availability :** Case 12 x 1 liter, 10 liters, 20 liters, 205 liters and aerosols (12 x 340 g).  
12 x 1 quart, 1 gallon, 5 gallons, 55 gallons, spray 12 x 12 oz.